

# TC-101S

## Cable air blower



### Product function

TC-101S Cable air blower is suitable for: 1~3mm optical cable 5~8mm communication microtubes. It is configured with a distance and speed counter to better control over the installation. It has the intelligent cable protection function, when the cable in the pipeline obstacles or external resistance can not be laid normally, the air blowing equipment will automatically protect the cable from damage.

### Product parameters

Cable dia(mm)	0.8-3.0	Max. air pressure(bar)	16
Duct OD(mm)	5-8	Equipment size(mm)	270x100x190
Drive unit	Electric adapter 12V	Dimension of case(mm)	620x420x410
Pushing force(N)	30	Weight of machine (kg)	6
Max.speed(m/min)	130	Total shippingweight(kg)	12

# TC-101M

## Cable air blower



### Product function

TC-101M Cable air blower is suitable for: 4~16mm optical cable 8~20mm communication microtubes. It is configured with a distance and speed counter to better control over the installation.

### Product parameters

Cable dia(mm)	4-16	Max. air pressure(bar)	16
Duct OD(mm)	8-20	Equipment size(mm)	600x400x300
Drive unit	Electric 220V	Dimension of case(mm)	650x450x350
Pushing force(N)	200	Weight of machine (kg)	20
Max.speed(m/min)	140	Total shippingweight(kg)	30